

Pressure Decay Leak detector

FC0730



- Clear display of leak and pressure
- Up to 50 test settings
- Pressure ranges from vacuum to 30bar
- 0.1Pa or 0.01cc/min leak resolution
- Front panel calibration port
- Front panel or remote start/stop
- Compact robust steel bench-top case
- Communications via RS232 or RS485

The FC0730 has much to offer as an entry level pressure decay Leak Detector. It is ideal for applications where multiple test-heads are needed, such as on a rotary table. It can be easily interfaced to PLCs or PCs where integration is required, or it may be used as a standalone instrument. The communications facility may be used for configuration, control and data logging.

Leak Measurement

Leak ranges	±200.0 Pa ±2.000 kPa ±20.00 kPa
Accuracy @ 20°C	200 Pa and 2 kPa models: 10% to 100% range: < ± (1% reading + 1 digit) 0 to 10% range: < ± (0.1% range + 1 digit) 20 kPa model: < ± (1% range + 1 digit)
Resolution	4 digit display
Temperature Coefficients	Zero: Automatic Span: < 0.15% per °C
Long Term Drift (span)	< ± 1% per year

Pressure Measurement

Pressure Ranges	± 99.99 mbar -1 bar to +4.000 bar -1 bar to +14.00 bar ± 200 mbar -1 bar to +8.000 bar -1 bar to +30.00 bar ± 999.9 mbar -1 bar to +9.999 bar
Accuracy @ 20°C	10% to 100% range: < ± (1% reading + 1 digit) 0 to 10% range: < ± (0.1% range + 1 digit)
Resolution	4 digit display
Temperature Coefficients	Zero: < 0.05% per °C Span: < 0.1% per °C
Long Term Drift (span)	< ± 1% per year

Electrical

Supply Voltage	24 VDC ± 10% < 500 mA
Electrical connections	Power: 2 way detachable screw terminal Outputs: detachable screw terminal Inputs: detachable screw terminal RS232: 9 pin D plug RS485: 5 pin detachable screw terminal
Control Inputs	Up to 12 Opto-isolated, active high or active low. 5 VDC to 24 VDC into 10 KΩ
Control Outputs	Up to 16 Active High transistor output (PNP). 12 VDC to 45 VDC, 120 mA (per channel)

Pneumatic

Media Compatibility	Clean dry air or non-corrosive gas
Air Supply Pressure	Maximum 10 bar gauge, Minimum 5 bar gauge
Regulator Supply Pressure	Maximum 16 bar gauge or 35 bar for 30 bar option
Pneumatic Connections	Air supply – 6 mm push-in tube connector Regulator supply and output – 8 mm push-in tube connector Test/Reference 1/8" BSPF Pneumatic pilot outputs - 4 mm push-in tube connectors
Leak Tightness	< 0.2cc/Hour
Media Compatibility	Clean dry air or non corrosive gas
Air Supply Pressure	Maximum 10 bar gauge, Minimum 5 bar gauge

Construction

Enclosure	Steel construction enclosure with paint finish. Suitable for 19" 3U rack mounting.
Dimensions – Rack Case	267 x 133 x 296 mm (W x H x D)
Dimensions – Bench Case	232 x 147 x 296 mm (W x H x D)
Weight	5 kg

28/05/2015

Furness Controls has a UKAS accredited laboratory which offers pressure calibration from 0 to 40 kPa and flow calibration from 0.1 ml/min to 2000 litres/min